

# FLAIR INTERLOGIX CROSS REFERENCE LIST

## MAGNETIC CONTACTS



REVISION 1019J

FLAIR P/N	INTERLOGIX CROSS	DESCRIPTION	QTY. PER BAG	COLORS
<b>VIP CONTACTS - NORMALLY CLOSED ONLY, LEAST EXPENSIVE</b>				
VIP100	1138T	Surface Mount Contact - CC, 7/8" Gap, 2" L x 1/4" W x 3/8" H, Terminals, Tabs, Mounting Tape, Vinyl Tape Cover	10	WHT, BRN, TAN
VIP1000-37	1045T	Surface Mount Contact - CC, 1 1/2" Gap, 4" L x 1/2" W x 1/2" H, Terminals, Gray	5	GRY
VIP1000-37S	1045	Surface Mount Switch Only - CC, 1 1/2" Gap, 4" L x 1/2" W x 1/2" H, 12" Jacketed Leads, Gray	5	GRY
VIP1000-98L	2202A-L	Overhead Door Contact - CC, 3" Gap, 3 1/2" L x 1 1/2" W, 18" Armored Cable, L-Bracket Magnet	1	ALUMINUM
VIP1000-98Z	2202AU	Overhead Door Contact - CC, 3" Gap, 3 1/2" L x 1 1/2" W, 18" Armored Cable, Z-Bracket Magnet	1	ALUMINUM
VIP130-2	1032W	Surface Mount Contact - CC, 7/8" Gap, 1 1/3" L x 1/3" W x 1/2" H, 18" Center #22AWG Leads, Mounting Tape	10	WHT, BRN, TAN
VIP39	1085T	Surface Mount Contact - CC, 1" Gap, 2 1/2" L x 1/2" W x 1/2" H, Terminals, Cover, Screws	10	WHT, BRN
VIP48	1078C	Recessed Contact - CC, 1/2" Gap in Steel, 3/4" X .870" Long, 12" #22AWG Leads	10	WHT, BRN
VIP48-1	1078C	Recessed Contact - CC, 1/2" Gap in Steel, 3/4" X .870" Long, Short Outer Body, 12" #22AWG Leads	10	WHT, BRN
VIP52	3015	Recessed Push Button Switch - CC, 3/4" Dia. x 1" L, 18" #22AWG Leads	10	WHT, BRN
VIP68	1055	Recessed Contact - CC, 3/4" Gap, 1/4" Dia. 1" Long, 18" #22 AWG Leads	10	WHT
VIP76	3015	Tamper Switch with Flange, CC, 3/8" Dia. x 1 1/2" Long, 18" #22AWG Wire Leads	10	WHT
VIP78	3012	Tamper Switch with Bracket, CC, 3/8" Dia. x 1 1/2" Long, 18" #22AWG Wire Leads	10	WHT
VIP88	1035	Surface Mount Contact - CC, 7/8" Gap, 1 1/2" L x 3/8" W x 1/4" H, 18" Center #22AWG Leads, Tape	10	WHT, BRN
VIP94-2	1125W	Recessed STUBBY Contact - CC, 5/8" Gap, 3/8" Dia. x 3/4" Long, 18" #22AWG Leads	10	WHT, BRN
VIP94-2N	R1125W	Recessed STUBBY Contact - CC, 3/4" Gap, 3/8" Dia. x 3/4" Long, 18" #22AWG Leads, MN400 Rare Earth Donut Magnet	10	WHT, BRN
VIP94-2T	1075T, 1125TW	Recessed Contact - CC, 5/8" Gap, 3/8" Dia. x 1" Long, Terminals	10	WHT, BRN
VIP94-2TN	R1125TW	Recessed Contact - CC, 3/4" Gap, 3/8" Dia. x 1" Long, Terminals, MN400 Rare Earth Magnet	10	WHT, BRN
<b>SURFACE MOUNT CONTACTS</b>				
1000-24S	1082	Surface Mount Contact - CC, 3/4" Gap, 2 1/2" L X 1/2" W X 1/2" H, 12" Jacketed Leads, Screw Mounting	10	WHT, BRN, GRY
1000-24W	1085TW	Surface Mount Contact - CC, 1 1/2" Wide Gap, 2 1/2" L X 1/2" W X 1/2" H, Terminals, Screw Mounting	10	WHT, BRN, GRY
1000-34	1087T	Surface Mount Contact - SPDT, 1" Wide Gap, 2 1/2" L X 1/2" W X 1/2" H, Terminals, Screw Mounting	10	WHT, BRN, GRY
1000-34S	1084D	Surface Mount Contact - SPDT, 1" Wide Gap, 2 1/2" L X 1/2" W X 1/2" H, 12" Jacketed Leads, Screw Mounting	10	WHT, BRN, GRY
1000-34SW RAC	1090	Recessed ANSI Contact - SPDT, 1" Gap, 4 7/8" L X 1 1/4" W X 5/8" D, 12" Jacketed Lead	1	WHT, BRN, GRY
1000-34SWY	1084D	Surface Mount Contact - DPDT, 1 1/2" Wide Gap, 2 1/2" L X 1/2" W X 1/2" H, 12" Jacketed Leads, Screw Mounting	10	WHT, BRN, GRY
1000-34W	1087TW	Surface Mount Contact - SPDT, 1 1/2" Wide Gap, 2 1/2" L X 1/2" W X 1/2" H, Terminals, Screw Mounting	10	WHT, BRN, GRY
1000-47	1047T	Surface Mount Contact - SPDT, 1 1/2" Gap, 4" L X 1/2" W X 1/2" H, Terminals, Screw Mounting	5	WHT, BRN, GRY
1000-47S	1047	Surface Mount Contact - SPDT, 1 1/2" Gap, 4" L X 1/2" W X 1/2" H, 12" Jacketed Leads, Screw Mounting	5	WHT, BRN, GRY
1000-50	1045TW	Surface Mount Contact - CC, 3" Gap, 4" L X 1/2" W X 1/2" H, Terminals, Screw Mounting	5	WHT, BRN, GRY
1000-50S	1045W	Surface Mount Contact - CC, 3" Gap, 4" L X 1/2" W X 1/2" H, 12" Jacketed Leads, Screw Mounting	5	WHT, BRN, GRY
1000-54	1044TW	Surface Mount Contact - SPDT, 3" Gap, 4" L X 1/2" W X 1/2" H, Terminals, Screw Mounting	10	WHT, BRN, GRY
1000-64L-36	2507A-L	Surface Mount Contact - Aluminum Gate Contact, SPDT, 3" Gap, 3 1/2" L X 2 1/2" W X 5/8" H, Waterproof, L-Bracket Magnet, 36" Armored Cable, Screw Mounting	1	ALUMINUM
1000-64SG	2317A	Clamp-On Overhead Door Contact - Aluminum Gate Contact, SPDT, 3" Gap, 3 1/2" L X 2 1/2" W X 5/8" H, Waterproof, 18" Armored Cable, Screw Mounting	1	ALUMINUM
1000-64YL-36	2507AD-L	Surface Mount Contact - Aluminum Gate Contact, DPDT, 3" Gap, 3 1/2" L X 2 1/2" W X 5/8" H, Waterproof, L-Bracket Magnet, 36" Armored Cable, Screw Mounting	1	ALUMINUM
1000-65L-36	2505A-L	Surface Mount Contact - Aluminum Gate Contact, CC, 3" Gap, 3 1/2" L X 2 1/2" W X 5/8" H, Waterproof, L-Bracket Magnet, 36" Armored Cable, Screw Mounting	1	ALUMINUM
1020-24	1285T	Surface Mount Contact - CC, 1" Gap, 2 1/2" L X 1/2" W X 1/2" H, Hidden Terminals, Screw Mounting	10	WHT, BRN, GRY

FLAIR P/N	INTERLOGIX CROSS	DESCRIPTION	QTY. PER BAG	COLORS
<b>1020-24W</b>	<b>1285TW</b>	Surface Mount Contact - CC, 1 1/2" Wide Gap, 2 1/2" L X 1/2" W X 1/2" H, Hidden Terminals, Screw Mounting	10	WHT, BRN, GRY
<b>LMS14-2</b>	<b>1034</b>	Surface Mount Contact - SPDT, 3/4" Gap, 1 1/4" L X 1/2" W X 1/4" H Break Away Flange, 12" #22AWG Center Leads, Screw Mounting or Tape	10	WHT, BRN
<b>LMS28</b>	<b>1085</b>	Surface Mount Contact - CC, 3/4" Gap, 2" L X 3/8" W X 3/8" H, 12" #22AWG Center Leads, Screw Mounting	10	WHT, BRN, GRY
<b>LMS29</b>	<b>1087</b>	Surface Mount Contact - SPDT, 3/4" Gap, 2" L X 3/8" W X 3/8" H, 12" #22AWG Center Leads, Screw Mounting	10	WHT, BRN, GRY
<b>LMS89</b>	<b>1037W</b>	Surface Mount Contact - SPDT, 3/4" Gap, 1 1/2" L X 3/8" W X 1/4" H, 12" #22AWG Center Leads, Tape	10	WHT, BRN, GRY
<b>1020-24</b>	<b>1285T</b>	Surface Mount Contact - CC, 1" Gap, 2 1/2" L X 1/2" W X 1/2" H, Hidden Terminals, Screw Mounting	10	WHT, BRN, GRY
<b>1020-24W</b>	<b>1285TW</b>	Surface Mount Contact - CC, 1 1/2" Wide Gap, 2 1/2" L X 1/2" W X 1/2" H, Hidden Terminals, Screw Mounting	10	WHT, BRN, GRY
<b>LMS14-2</b>	<b>1034</b>	Surface Mount Contact - SPDT, 3/4" Gap, 1 1/4" L X 1/2" W X 1/4" H Break Away Flange, 12" #22AWG Center Leads, Screw Mounting or Tape	10	WHT, BRN
<b>LMS28</b>	<b>1085</b>	Surface Mount Contact - CC, 3/4" Gap, 2" L X 3/8" W X 3/8" H, 12" #22AWG Center Leads, Screw Mounting	10	WHT, BRN, GRY
<b>LMS29</b>	<b>1087</b>	Surface Mount Contact - SPDT, 3/4" Gap, 2" L X 3/8" W X 3/8" H, 12" #22AWG Center Leads, Screw Mounting	10	WHT, BRN, GRY
<b>LMS89</b>	<b>1037W</b>	Surface Mount Contact - SPDT, 3/4" Gap, 1 1/2" L X 3/8" W X 1/4" H, 12" #22AWG Center Leads, Tape	10	WHT, BRN, GRY
<b>SURFACE MOUNT AND OHD HIGH SECURITY CONTACTS</b>				
<b>1000-64Y-36 BMS</b>	<b>2507AH</b>	Heavy Duty High Security Surface Mount Balanced Magnetic Contact - SPDT with SPDT Magnetic Tamper, 0" TO 1/2" Area of Operation, 3 1/2" L X 2 1/2" W X 5/8" H, Waterproof, 18" Armored Cable, Screw Mounting	1	ALUMINUM
<b>1000-64YL-36 BMS</b>	<b>2507AH-L</b>	Heavy Duty High Security Surface Mount Balanced Magnetic Contact - SPDT with SPDT Magnetic Tamper, 0" TO 1/2" Area of Operation, 3 1/2" L X 2 1/2" W X 5/8" H, Waterproof, L-Bracket Magnet, 18" Armored Cable, Screw Mounting	1	ALUMINUM
<b>1000-98LY-36 BMS</b>	<b>2207AH-L</b>	High Security Overhead Door Balanced Magnetic Contact - SPST with Magnetic Tamper, 1" to 2 3/4" Area of Operation, 3 1/2" L X 2 1/2" W X 5/8" H, Waterproof, 36" Armored Cable, Screw Mounting, L-Bracket Magnet	1	ALUMINUM
<b>MSS2707AL-36</b>	<b>2707A-L</b>	High Security Triple Bias Balanced Magnetic Switch (BMS), SPDT (three wires), CC Pry Tamper (two wires), Aluminum Extruded Case, 4 1/4" L x 1 1/2" W x 3/4" D, Sealed with Urethane Potting, Operating Gap, 0.3" - 0.6", 1/8" Thick Pry Tamper Magnet Spacer mounts behind switch against door frame, L-Bracket Magnet, 36" Armored Cable, 24" #22 AWG wires	1	ALUMINUM
<b>MSS2757</b>	<b>2757</b>	Recessed High Security Triple Biased Magnetic Contact, SPDT Configuration with Tamper Loop, 1/2" Gap, 1 3/8" Deep with 1 1/4" W x 4 7/8" L ANSI Plate, Jacketed Leads	1	STAINLESS STEEL
<b>RECESSED CONTACTS</b>				
<b>MSS100-4</b>	<b>1076</b>	Recessed Contact - SPDT, 1/2" Gap in Steel, 1" Dia. X 7/8" L, 12" #22AWG Leads	10	WHT, BRN, GRY, BLK
<b>MSS100-4W</b>	<b>1076W</b>	Recessed Contact - SPDT, 1" Wide Gap in Steel, 1" Dia. X 7/8" L, 12" #22AWG Leads	10	WHT, BRN, GRY, BLK
<b>MSS100-4Y</b>	<b>1076D</b>	Recessed Contact - DPDT, 1/2" Gap in Steel, 1" Dia. X 7/8" L, 12" #22AWG Leads	10	WHT, BRN, GRY, BLK
<b>MSS100-6</b>	<b>1078</b>	Recessed Contact - CC, 1/2" Gap in Steel, 1" Dia. X 7/8" L, 12" #22AWG Leads	10	WHT, BRN, GRY, BLK
<b>MSS100-6W</b>	<b>1078W</b>	Recessed Contact - CC, 1" Wide Gap in Steel, 1" Dia. X 7/8" L, 12" #22AWG Leads	10	WHT, BRN, GRY, BLK
<b>PFC40</b>	<b>1078CT</b>	Recessed Contact - CC, 1/2" Gap in Steel, 3/4" Dia. x 1 1/4" Long, Terminals (VIP48T)	10	WHT, BRN, GRY, BLK
<b>PFC40-1</b>	<b>1078CT</b>	Recessed Contact - CC, 1/2" Gap in Steel, 3/4" Dia. x 1 1/4" Long, Short Outer Body, Terminals (VIP48-1T)	10	WHT, BRN, GRY, BLK
<b>PFC42</b>	<b>1076C</b>	Recessed Contact - SPDT, 1/2" Gap in Steel, 3/4" Dia. X 7/8" L, 12" #22AWG Leads	10	WHT, BRN, GRY, BLK
<b>PFC42W</b>	<b>1076CW</b>	Recessed Contact - SPDT, 1" Wide Gap in Steel, 3/4" Dia. X 7/8" L, 12" #22AWG Leads	10	WHT, BRN, GRY, BLK
<b>PFC48</b>	<b>1078C</b>	Recessed Contact - CC, 1/2" Gap in Steel, 3/4" Dia. X 7/8" L, 12" #22AWG Leads	10	WHT, BRN, GRY, BLK
<b>PFC48W</b>	<b>1078CW</b>	Recessed Contact - CC, 1" Wide Gap in Steel, 3/4" Dia. X 7/8" L, 12" #22AWG Leads	10	WHT, BRN, GRY, BLK
<b>RMS56K</b>	<b>1072</b>	Recessed Contact - CC, 3/4" Gap, 3/8" Dia. X 1" L w/ 3/4" Dia. Flange, 12" #22AWG Leads	10	WHT, BRN
<b>RMS56KW</b>	<b>1072W</b>	Recessed Contact - CC, 1 1/4" Wide Gap, 3/8" Dia. X 1" L w/ 3/4" Dia. Flange, 12" #22AWG Leads	10	WHT, BRN
<b>RMS60K</b>	<b>1073</b>	Recessed Contact - OC, 3/4" Gap, 3/8" Dia. X 1" L w/ 3/4" Dia. Flange, 12" #22AWG Leads	10	WHT, BRN
<b>RMS60KW</b>	<b>1073W</b>	Recessed Contact - CC, 1 1/4" Wide Gap, 3/8" Dia. X 1" L w/ 3/4" Dia. Flange, 12" #22AWG Leads	10	WHT, BRN
<b>RMS68-1</b>	<b>1058</b>	Recessed Contact - CC, 1/2" Wide Gap, 1/4" Dia. X 1/2" L, 12" #22AWG Leads	10	BLK

FLAIR P/N	INTERLOGIX CROSS	DESCRIPTION	QTY. PER BAG	COLORS
<b>RMS69-2</b>	<b>1016, 1017, 1052, 1053</b>	Recessed Contact - SPDT, 3/4" Gap, 1/4" Dia. X 3/4" L, 12" #22AWG Leads	10	BLK
<b>RMS94-2N</b>	<b>R1125W</b>	Recessed STUBBY Contact - CC, 3/4" Gap, 3/8" Dia. X 3/4" L, 12" #22AWG Leads, MN400 Magnet	10	WHT, BRN
<b>RMS94W-2</b>	<b>1075W</b>	Recessed STUBBY Contact - CC, 1 1/4" Wide Gap, 3/8" Dia. X 3/4" L, 12" #22AWG Leads	10	WHT, BRN
<b>RMS95-2</b>	<b>1070</b>	Recessed STUBBY Contact - SPDT, 3/4" Gap, 3/8" Dia. X 3/4" L, 12" #22AWG Leads	10	WHT, BRN
<b>RMS95W-2</b>	<b>1070W</b>	Recessed STUBBY Contact - SPDT, 1" Wide Gap, 3/8" Dia. X 3/4" L, 12" #22AWG Leads	10	WHT, BRN
<b>OVER HEAD DOOR CONTACTS</b>				
<b>1000-38Z</b>	<b>2515A</b>	Surface Mount Contact - CC, 3" Gap, 8" L X 1 3/4" W X 1/2" H, Z Magnet Bracket, 18" Armored Cable, Screw Mounting	1	WHT, BRN, GRY
<b>1000-50SG</b>	<b>2315A</b>	Clamp-On Overhead Door Contact - CC, 3" Wide Gap, 4" L X 1/2" W X 1/2" H, 72" Jacketed Leads, Screw Mounting, Gray	1	GRY
<b>1000-96L</b>	<b>2204A-L</b>	Surface Mount Contact - SPDT, 3" Gap, 3 1/2" L X 1 3/4" W X 1/2" H, L-Bracket Magnet, 18" Armored Cable, Screw Mounting	1	ALUMINUM
<b>1000-96Z</b>	<b>2204AU-L</b>	Surface Mount Contact - SPDT, 3" Gap, 3 1/2" L X 1 3/4" W X 1/2" H, Z-Bracket Magnet, 18" Armored Cable, Screw Mounting	1	ALUMINUM
<b>1000-96ZY-36</b>	<b>2207AD-L</b>	Surface Mount Contact - DPDT, 3" Gap, 3 1/2" L X 1 3/4" W X 1/2" H, Z-Bracket Magnet, 36" Armored Cable, Screw Mounting	1	ALUMINUM
<b>1000-98L</b>	<b>2202A-L</b>	Overhead Door Contact - CC, 3" Gap, 3 1/2" L x 1 1/2" W, L-Bracket Magnet, 18" Armored Cable	1	ALUMINUM
<b>1000-98LY-36 BMS</b>	<b>2207AH-L</b>	High Security Overhead Door Balanced Magnetic Contact - SPST with Magnetic Tamper, 1" to 2 3/4" Area of Operation, 3 1/2" L X 2 1/2" W X 5/8" H, Waterproof, 36" Armored Cable, Screw Mounting, L-Bracket Magnet	1	ALUMINUM
<b>1000-98Z</b>	<b>2202AU-L</b>	Overhead Door Contact - CC, 3" Gap, 3 1/2" L x 1 1/2" W, 18" Armored Cable, Z-Bracket Magnet	1	ALUMINUM
<b>PULL APART SWITCH</b>				
<b>PA1000-80</b>	<b>2105A</b>	Heavy Duty Pull Apart Switch - CC, 3 1/2" L X 2 1/2" W X 5/8" H, Waterproof, 36" Armored Cable, Screw Mounting	1	BRN
<b>PA1000-81</b>	<b>2107A</b>	Heavy Duty Pull Apart Switch - SPDT, 3 1/2" L X 2 1/2" W X 5/8" H, Waterproof, 36" Armored Cable, Screw Mounting	1	BRN
<b>ACCESSORIES</b>				
<b>316</b>	<b>19442-L</b>	Equal Leg L-Bracket, 2" Legs x 4" L	1	ALUMINUM
<b>319</b>	<b>1944-L</b>	Z-Bracket, 1" Legs x 5/8" Rise x 4" L	1	ALUMINUM
<b>HAC732-300</b>	<b>1980-25</b>	25 Feet, 7/32" Stainless Steel Square Lock Tubing	1	NOT APPLICABLE